HANRUN PAPER DTF PRO-A600

Hanrun paper PRO-A600DTF printer is a DTF printer specially develop for those customers who pursue high quality and mass production. The Pro series is a high-end flagship series developed by us, compared with the EVO series, the pro series has higher continuous printing stability, more software compatibility, beter printing fineness and it also has a half year longer warrenty. The DTF printing device is the market's most advanced DTF solution. In comparison to other hardware systems, the DTF printer has a lot of advantages compares to other mahcines (including Toner Transfer, or even high-end DTG).

Works on both withe and dark textiles and works with a variety of fabric styles (cotton, poly blends, leather, denim and more).

- High-end flagship
- Continuous printing stability
- Better software compatibility
- Better productivity

KEY PRODUCT FEATURES

- The most high-end flagship DTF printer
- Higher continuous printing stability and fineness
- Larger width, 30%-50% better productivity than Evo series
- Better software compatibility
- Longer warranty time and more gift accessories

APPLICATION

- Washing labels; all kinds of socks
- Fashion cloths
- Personalized customization

DTF EVO-A600 PRINTER

Model	DTF PRO-A600 printer (2 heads)	DTF PRO-A600 printer (4 heads)
Printhead	EPSON i3200	
Print Resolution/Speed	4pass(360*2400dpi); 14m²/h 6pass(360*3600dpi); 10m²/h 8pass(720*2400dpi); 8m²/h	4pass(360*2400dpi); 24m²/h 6pass(360*3600dpi); 16m²/h 8pass(720*2400dpi); 12m²/h
Ink	pigment ink (CMYK+W)	
Method of ink supply	Continuous supply + white-ink circulation system	
Print wide	600mm	
Print media	DTF film	
Media transfer	Automatic receiving and discharging membrane system	
Heating device	Heat in the fron, middle and rear section	
Transfer interface	Ethernet	
Consumption	Dual-head I3200 Machine Print 4pass 14m²/h, four-head 24m²/h, one roll film 60 square, a pack of 20kg powder a set of color ink, can print 4-5 rolls.	
Voltage	AC110V/220V (±10%) 50HZ/60HZ	
Working environment	Temperature 20-28°C Humidity 40-70%RH	
Power	1Kw	
Software compatibility	MainTop6.1/Photoprint19/UltraPrint/neoStampa/Wasatch/ONXY	
Printer size	L1660mm*W750mm*H1620mm	
Printer net weight	129kg	

SMOKE PURIFIER

Air inlet diameter	Φ 50mm
Voltage	AC220V 50HZ/60HZ
Output Power	300W
Filter effect	0.3um 99%
Noise volume	50-60db
Size	L410mm*W400mm*H295mm
Weight	10kg

POWDER SHAKER B601 (2 HEADS)

Arch bridge stainless steel air-free platform effectively extends the heating duration of the medium in the tunnel

POWDER SHAKER B602 (2 HEADS)

Automated track advancement, based on air suction platform, very flexible, more suitable for single cutting & roll baking, effectively prevent medium baking arch deformation, constant temperature heating in the tunnel heat evenly

POWDER SHAKER

Model	B601 (2 heads)	B602 (4 heads)
Power	5.22KW	7.8KW
Powder shaker Dimensions	L1985mm*W1090mm*H1080mm	L2090mm*W1090mm*H1080mm
Net Weight	110kg	
Match model	A 2-head DTF printer (inquir for a 4-head model matching)	
Temperature control scope	0-170ºC	
Speed regulation range	Synchronize with printer speed	
Maximum heating pipe power	5Kw	
Medium width	0-600mm	
Method of transmission	Conductor traction	Two kinds: tractor+belt transmission
Automatic volume collection	✓	✓
Upper powder device	Top manual powder direction and powder amount automatically control	
Refer to powder device	Bottom powder box, need manual powder return	
Air suction device	x	x
Upper powder device	✓	
Consumption	Energy consumption 1.5-4.3KW	Energy consumption 2.3-5KW
Work environment	15-30°C 45-65%RH	

Hanrun paper®
Transfer to Digital Transfer to Future

If you need help, please log in to our official website: *www.hanrunpaper.com*

Contact us

Address :403, No.10 building, Baijiahui Innovation Community, 699-18 Xuanwu Avenue, Nanjing, China
Mobile Phone :008617714537154
Email :info@hanrunpaper.com

Screen • Pad • Digital • Laser Equipment
CHEMOSOL
Chemicals • Substrates • Printing Supplies
22 Trump str, Selby, Johannesburg
011 493 3686 • 011 058 3500
www.chemosol.co.za • info@chemosol.co.za